

Ringling current - internal sound ringling WK 954 AP



The sound ringling secondary device with condensator and optic indication is used as additional signalling for telephones in indoor room in surface version.

The **connection** of the sound ringling secondary device is carried out selectable via **a - b** or **w - wire**.

Possible application areas:

- telecommunication
- industry
- end user
- for use in telecommunication networks
can be utilised throughout Europe

Features:

- electronic three-tone ringling, adjustable in volume and sound impression (sequencer frequency)
- optic indication of ringling via illuminated diode
- surface version

Technical data:

volume (small reverberant room)

operating voltage

frequency range

impedance at 50 V ~

sequencer frequency at 25 Hz

sound frequencies

housing made from thermoplastic

radio interference degree N

cable insertion selectable from above or below

weight

colour

dimensions L x W x H approx. in mm

≥ 98 dB (A)

25 - 60 V ~

23 - 54 Hz

≥ 8 kW

2.5 - 25 Hz adjustable

800 Hz, 1.067 Hz, 1.333 Hz

70 g

pearl white / RAL 1013

80 x 65 x 31.5

Article no.:

60164

Authorisations:

- ZZF-authorisation 119/024
- CE-marking

Applications:

- for indoor rooms
- for additional signalling in rooms
in without a telephone