

# Ringling current - internal sound ringling

## WK 958 UP



The sound ringling secondary device with condensator and optic indication is used as additional signalling for telephones in indoor rooms in flush version.

A telephone with TAE - plug coding F can be plugged directly into the sound ringling secondary device.

### Possible application areas:

- telecommunication
- industry
- end user
- for use in the telecommunication network

### Features:

- electronic three-tone ringling, adjustable in volume and sound impression (sequencer frequency)
- optic indication at incoming call is carried out via illuminated diode
- flush version

### Technical data:

volume (small reverberant room)  
operating voltage  
frequency range  
impedance at 50 V ~  
sequencer frequency at 25 Hz  
sound frequencies  
housing made from thermoplastic  
radio noise interference degree N  
for UP - socket d = 58 mm (switch socket)  
weight  
colour  
dimensions L x W x H approx. in mm

### Part no.:

60189

### Authorisations:

- BZT-authorisation A350102C
- CE-marking

### Applications:

- for indoor rooms
- for additional signalling in rooms without a telephone

≥ 98 dB (A)  
25 - 60 V ~  
23 - 54 Hz  
≥ 8 kW  
2.5 - 25 Hz adjustable  
800 Hz, 1.067 Hz, 1.333 Hz

75 g  
pearl white / RAL 1013  
80.5 x 80.5 x 47