

Ringling Current - internal sound ringing WK 958 AP



The sound ringing secondary device with condensator and optic indication is used as additional signalling for telephones in indoor rooms in surface version.

A telephone with TAE-plug coding F can be plugged directly into the sound ringing secondary device.

The **connection** of the sound ringing secondary device is carried out selectable via **a - b** or **w - wire**.

Possible application areas:

- telecommunication
- industry
- end user
- for use in the telecommunication network

Features:

- electronic three-tone ringing, adjustable in volume and sound impression (sequencer frequency)
- optic indication by incoming call via illuminated diode
- surface version

Technical data:

volume (small reverberant room)
operating voltage
frequency range
impedance at 50 V ~
sequencer frequency at 25 Hz
sound frequencies
housing made from thermoplastic
radio noise interference degree N
cable insertion selectable from above or below
weight
colour
dimensions L x W x H approx. in mm

Part no.:

60188

Authorisations:

- BZT-authorisation A350100C
- CE-marking

Applications:

- for indoor rooms
- for additional signalling in rooms in without telephone

≥ 98 dB (A)
25 - 60 V ~
23 - 54 Hz
 ≥ 8 kW
2.5 - 25 Hz adjustable
800 Hz, 1.067 Hz, 1.333 Hz

75 g
pearl white / RAL 1013
80 x 65 x 31.5